

POS PRINTER



LK-TL200

- Energy star qualified for power efficiency
- High speed printing : 200mm/sec
- Paper width adjustable 50~82.5mm
- ESC/POS command compatible
- Accessories : Melody box, spillproof cover
- Wall mount installation available
- Various O/S drivers : Windows Driver(2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit), Windows CE & Mobile Driver & SDK(CE 4.2 ~, Mobile 5.0 ~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(2.1 ~) SDK, Windows SDK



APPLICATIONS



Shopping



Mart



Airport



Hospital



Coffee Shop



Bank



Restaurant



Ticketing



Parking




Lottery



Election

EASY-LOAD DESKTOP THERMAL POS PRINTER

LK-TL200



MODEL		LK-TL200
PRINTING	METHOD	Direct Thermal
	SPEED	Max. 200mm/sec
	WIDTH	72mm(512 Dots/Line)
	RESOLUTION	180DPI
PAPER	TYPE	Thermal Paper
	WIDTH	50mm ~ 82.5mm
	THICKNESS	0.06mm ~ 0.09mm
	ROLL DIAMETER	Max. \varnothing 80.0mm
	ROLL CORE INNER	12.5mm \pm 0.5mm
RELIABILITY	TPH LIFE	160km
	MCBF	60,000,000Lines
AUTO CUTTER		1,500,000cuts(Guillotine)
SENSOR	STANDARD	Paper End, Paper Low, Cover Open
	OPTION	Black Mark Sensor
INTERFACE		USB (B type) + Serial Build-in
EMULATION		ESC/POS Command Compatible
DRIVER		Windows Driver(2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit), Windows CE & Mobile Driver & SDK(CE 4.2 ~, Mobile 5.0 ~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(2.1 ~) SDK, Windows SDK
POWER	TYPE	External SMPS
	AC	100 ~ 240Vac 50/60 Hz
	DC	24Vdc / 1.75A
TEMPERATURE	OPERATION	5 ~ 40°C
	STORAGE	-20 ~ 60°C
DIMENSION		152 x 204 x150 mm (W x D x H)
WEIGHT		1.7kg
COLOR		Cool grey, Ivory

INTERFACE



ACCESSORY



Spill proof cover



Melody box



SEWOO TECH Co., Ltd.

374-2, Gajang-dong, Osan-si, Gyeonggi-do, 447-210, Korea

T. +82-31-459-8200 F. +82-31-459-8880

www.miniprinter.com

